

Data Sheet

For part # FF-HTCRMP-3

Crimp size: Hex Dia sizes

- 3.25mm
- 3.65mm
- 4.52mm



Process: Heavy Duty Crimping

Product Name: POF Crimping tools

Service Crimping Tools, PEW16 frame

Description:

- guaranteed optimal, solder less, electrical connections
- best crimping quality by means of an exact crimp motion and precision dies
- reduced hand force due to optimal lever transmission
- forced locking system (release able) leads to a reliable crimping result
- adjustable crimping pressure
- convenient handling due to ergonomically designed handles
- one or two hand operation
- material: special temper-hardened tool steel
- finish: burnished head, red plastic handles
- for different application

Model No.: PEW 16

Finish Type: burnished

Handles: plastic coated

Length: 250 mm

Weight: 550 g

Others: FF-HTCRMP-2

For service call: FiberFin technical department

630-553-6924 ext 114 8-5pm CST

Email: technical questions or comments to: Sevice@fiberfin.com

Optional Crimp dies:

Note: these are special order from Germany

FOB: Germany

Art. No.	Modell Model	Anwendungsbereich Range of application	Profil Profile	Verbinder Connectors	Crimpstellen Crimp nests	Kapazität Capacity mm ²	AWG
626 020 3	PEW 16.2	unisierte Verbinder non-insulated connectors			3	0,25-2,5	23-13
626 030 3	PEW 16.3	unisierte Verbinder non-insulated connectors			3	4,0-10,0	12-7
626 031 3	PEW 16.31	unisol. Stoßverbinder • non-insulated splice connectors			5	1,5-10,0	15-7
626 032 3	PEW 16.32	unisierte Verbinder non-insulated connectors			4	0,5-10,0	20-7
626 033 3	PEW 16.33	unisierte Verbinder non-insulated connectors			2	16 + 25	5 + 3
626 045 3	PEW 16.45	unisol. Flachsteckverb. • non-insulated plug connectors			4	0,1-2,5	27-13
626 050 3	PEW 16.5	unisol. Flachsteckverb. • non-insulated plug connectors			3	0,5-6,0	20-10
626 674 3	PEW 16.674	Modulstecker modular plugs			4	0,5-2,5	20-13
626 053 3	PEW 16.53	gerollte Kontakte rolled contacts			3	0,14-1,5	26-15
626 060 3	PEW 16.6	isolierte Verbinder insulated connectors			3	0,5-6,0	20-10
626 060-3 3	PEW 16.6-3	Schrumpfschlauchverbinder headshrink splices			3	0,5-6,0	20-10
626 063 3	PEW 16.63	isolierte Verbinder insulated connectors			2	10-16	7-5
626 071 3	PEW 16.71	gedrehte Kontakte turned contacts			4	0,14-4,0	25-11
626 072 3	PEW 16.72	gedrehte Kontakte turned contacts			4	1,5-6,0	15-10
626 090 3	PEW 16.9	Aderendhülsen isol. und unisoliert • end sleeves, insulated and non-insulated			5	0,25-6,0	23-10
626 091 3	PEW 16.91	Aderendhülsen isol. und unisoliert • end sleeves, insulated and non-insulated			3	10-25	7-3
626 092 3	PEW 16.92	Aderendhülsen isol. und unisoliert • end sleeves, insulated and non-insulated			2	35+50	2+1/0
626 097 3	PEW 16.97	Twin-Aderendhülsen Dual entry ferrules			3	2 x 6,10,16	2 x 10,7,5
626 100 3	PEW 16.10	Koax-Verbinder Coax connectors			3	RG 58, 59, 62, 71	
626 110 3	PEW 16.11	Koax-Verbinder Coax connectors			3	RG 58, RG 174	

For service call: FiberFin technical department

630-553-6924 ext 114 8-5pm CST

Email: technical questions or comments to: Sevice@fiberfin.com