

Product Specifications

Product No: Part # FF-HEB1.5/2.2

1. Scope

This specification covers basic requirements for the structure and optical performances of FF-HEB1.5/2.2.

End Emitting Fiber, 1.5mm dia. fiber with a 2.2mm dia. black PE jacket

2. Structure

Product Data: 1. Fiber core material MMA Polymer 2. Cladding material PTFE 3. Jacket material Black PVC 4. Minimum bending radius 6 x diameter 5. Wavelength range 400-700nm 6. Interior Refractive Index 1.475		
--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------	--	--

Specifications:

Item		Unit	Index	Testing method
Structural Parameters	Core diameter	mm	1.5	JIS C 6863
	Outer diameter	mm	2.2	
	Cladding non-circularity	%	≤6	
	Length	m/roll	100	
Optical Properties	Attenuation	dB/km	≤700	650nm JIS C 6863
	Numerical Apertures	/	0.68	
	Attenuation (95% RH)	dB/km	300-350	
Mechanical Properties	Repeated bending (200times)	dB	Loss added ≤2	JIS C 6861
	Tensile strength	N	70	
	Twisting (5times)	dB	Loss added ≤2	
	Impacting (0.4N/meter)	dB	Loss added ≤2	

Operating temperature: -40°C to 70°C

Recommended Storage temperature: -10°C to 35°C