

## **OM-Giga-DE075**

### ***Gradient-Index Plastic Optical Fiber***

OM-Giga is a poly(methyl methacrylate)-based GI-POF for high-speed short-distance data-communication applications. It does not contain any refractive-index modifying dopant, and has excellent mechanical properties and thermal stability.

<b>Property</b>	<b>DE-075</b>	<b>Remarks</b>
Fiber Diameter (core)	0.75 (0.675) mm	
Variation of Fiber Diameter	$\pm 5\%$	95% confidence interval
Jacket Diameter (minor axis / major axis)	2.2 / 4.4 mm	
Variation of Jacket Diameter	$\pm 5\%$	
Jacket Material	Polyethylene	Black or blue
Type of cable	Duplex	
Tensile Strength	$> 40$ N	at break
Bending Radius	25 mm	
Operating Temperature	$-30 \sim 70$ °C	
Attenuation at 650 nm	$< 220$ dB/km	measured by OTDR
Bandwidth	$> 3.0$ Gbps	at 50 m

For additional information, please contact us at

Optimedia, Inc.  
204 Byuksan Technopia, 560 Dunchon-daero, Jungwon-gu,  
Seongnam-si, Gyeonggi-do, 13230, Korea

Tel : +82-31-737-8151 Fax : +82-31-737-8150  
e-mail: cwpark@omgiga.com (cwpark14@gmail.com)